Achieving Operational Excellence on a Continuous Process with Severe Disturbances: A DeltaV APC Project

Leveraging Embedded APC Technology and SmartProcess Applications





Photography & Video Recording Policy



Photography and audio/video recording is not permitted in any session, or in the exhibition areas, without press credentials or written permission from the Emerson Exchange Board of Directors. Inquiries should be directed to:

EmersonExchange@Emerson.com

Thank you!



Presenters



Eric Wheatcroft

James Beall

John Ward









Introduction

- Process Overview
- Successful APC Execution Plan
- Business Results Achieved
- Summary
- Where To Get More Information



Emerson Global Users Exchange

Process Overview – Delayed Coking

- Thermal process, Vacuum Resid rapidly heated and contained in a coke drum.
 - Process is endothermic (heat of reaction supplied by furnace)
- Three Distinct Steps
 - Partial vaporization and mild cracking of feed in furnace
 - Cracking of vapors as flow passes through coke drum
 - Successive cracking and polymerization of hydrocarbons in coke drum
- Yields and Product Quality are a function of temperature, pressure, and throughput ratio (fresh feed + recycle)/fresh feed
- Increase in coking temp decreases coke production



3

Process Overview - PFD





Process Overview - PFD









Process <u>Unmeasured</u> & <u>Unquantified</u> Disturbances

- Drum Cycles
 - Backwarm
 - Drum Switches
- HCGO Pall Filter Switches
 - HCGO pumparound integrated into the product circuit
 - Amplified the effects of <u>HOURLY</u> Pall filter switches
- Control Induced Variability
 - Feed pump spillback pressure control valve
 - Tower reflux flow control valve



Continuous Process with Severe Disturbances



- What would you do if your fractionator is in equilibrium and the V/L, feed rate, feed composition, heat input, suddenly changed by 20% – 30%?
- Leave and go fishing!
- Effects
 - Tray Weeping
 - Equilibrium disturbances (Vapor Liquid Mass Transfer)
 - Off Spec Product and less yield
 - Major compensation moves by operators





Challenges:

- Continuous process with significant cyclic disturbances
 - Inconsistent operator response to process disturbances
 - Product quality and yield variation
- Project Objectives:
 - Compensate for disturbances
 - Maximize LCGO production
 - Minimize product quality (Naphtha, LCGO) variation
- APC facilitates:
 - Automates and optimizes "Best operator responses"
 - Control loops in desired modes
 - Minimize operator intervention



APC Development



Justification

- Internal Sponsorship
- ROI Assessment
- System Preparation
 - Control Foundation Analysis & Improvement
- APC Execution
 - Embedded MPC and SmartProcess[®] Composites
 - Model Identification & Validation
 - Optimizer Objective Function Definition
- Quantify Benefits





- Extensive review of process, equipment, problems, and project objectives
- Estimate Yield and Financial results achievable with APC
- APC Implementation Plan including valve/instrument repairs
- Obtain support of operations and management





- Analyze key control loops, not just tune loops!
- Goal to improve PROCESS performance not just "LOOP" performance
- Review control metrics with DeltaV InSight
- Review control configuration and scheme
- Maximize PROCESS performance





- Assess equipment installation against best practices
- Assess general type and condition of control valves and instrumentation
- Operator interviews
 - Facilitates better understanding of the process
 - Understand control problems and operator responses
- Scope for APC Project
 - Reviewed and analyzed 30 key loops
 - Found issues with 3 key instrument and 2 critical valves
 - "Significant" (>30%) tuning changes on 27 of 30 loops
 - Recommended new control scheme on critical equipment









Fractionator Reflux Control Valve (Temp to Flow Cascade)





Results

- Significant (>30%) reduction in variability on 10/30 of the loops
- Found opportunity for small MPC to increase waste heat recovery - \$70K/year benefit!
- Identified critical valves that required maintenance
- Reduces time required to implement APC
- Increases benefit of APC projects
 - Coordinated control loop responses contribute to project success
- Provides 25-50% of benefit of total APC project!

APC Execution – Embedded Model Predictive Clobal Control

- MPC Model Predictive Control
- Special control block in DeltaV
 - Multiple inputs
 - Multiple outputs
 - Dynamic matrix controller
 - Linear Program Optimizer
- Uses models to predict future trajectory of the controlled variables
- Optimizer achieves process/economic objectives





Embedded MPC - Types Of Process Variab

- Manipulated Variables (MV) Valves or controller setpoints written to by the MPC.
- Disturbance Variables (DV) Measured variables which may also affect the value of controlled variables
- Controlled Variables (CV) Process variables which are to be maintained at a specific value; i.e., the setpoint
- Constraints (Limit) Variables (LV) Variables which must be maintained within an operating range (a special type of CV)

APC Execution - SmartProcess® Applications



- Pre-Engineered APC Applications
- MPC and NN licenses
- Application specific calculations
- KPI's
- Regulatory control configuration
- Simulated process and example APC solution
- Configuration guide
- Implementation services (optional)



APC Execution - SmartProcess®











Process models, input to output, are derived from observed step tests of









- DeltaV PredictPro Automate MV step testing routine and determine models
- Emerson's EnTech Toolkit determine models very accurately
 - Many models were available from the control foundation project, so we continued full model analysis with Toolkit
- PredictPro validate models from any source





APC Execution – CHS MPC Variables

- Controlled Variables (CV) -Process variables which are to be maintained at a specific value; i.e., the setpoint
 - Naphtha Draw Comp Temp
 - LCGO Draw Comp Temp
 - HCGO Draw Comp Temp
- Manipulated Variables (MV) Controller setpoints written to by the MPC.
 - Ovhd Temp (TC751285)
 - Net LCGO (FIC751349)
 - Lean Oil to E7610 (FIC
 - HCGO P/A (FIC751288)
 - Total Wash Oil (FC75

- Constraints (LV) Variables which must be maintained within an operating range (a special type of CV)
 - Debut Reboiler Bypass Valve
 - Frac Ovhd Rec LIC Out
 - Sponge Oil Static Head
 - LCGO To Strpr Vlv
 - Etc.
- Disturbance Variables (DV) -Measured variables which may also affect the value of controlled variables
 - Backwarm (calculated)
 - Drum Switch (calculated)
 - Fresh Feed
 - Reflux Flow
 - Reflux Temp
 - Coke Drum Quench Temp
 - Etc.













PredictPro Automated Step Testing



Process Models in MPC block







- Measurements are not available for Backwarm and Drum Switch
- Created "calculated" DV's for Backwarm and Drum Switch
- Backwarm
 - Reduction in heat input to the Fractionator
 - Change in composition to the Fractionator
 - Created a DV with scale 0-100%, reduce from 100 to 80 when triggered

Drum Switch

- Reduction in heat input to the Fractionator
- Minor change in composition to the Fractionator
- Created a DV with scale 0-100%, reduce from 100 to 70



- Each DV triggered with key process variables and associated switching valves
- DV's ramped slowly back to 100% after event to "rearm"
- Calculated the models for both DV's
 - Knowing approximately how much key MV's would move to compensate for the heat and composition change
 - Use the opposite amount of MV move, multiplied by know
 MV to CV/LV models to obtain the model from the calculated
 DV's



APC Execution – Validate MPC Process Models







APC Execution – MPC Optimizer – Linear Program









APC Execution – Performance



Minimal deviation during major disturbance!





- Eliminated operator intervention during coke drum backwarm and drum switch operations!
- The average LCGO production was increased by almost 5% of rate which resulted in a payback of 6 months for the project!
- Reduced downstream unit constraint
 - Shifted HCGO production to LCGO Right barrels in the right place!
- Reduced Naphtha quality exceedances by 32%, LCGO by 40%
- ROI < 6 months!</p>
- Management & Operators gained confidence in





Summary

- APC can be successful on process with large unmeasured disturbances
- Implementation plan ensures success
 - Project Sponsor
 - Benefit Assessment
 - Control Foundation Improvement
 - Embedded MCP and SmartProcess[®] Application Package saves time
- Reduced product quality exceedances by >32%
- ROI on project was 6 months!
- Identified other opportunities
- Questions





Where To Get More Information

- Other EGUE Sessions
 - TBD
- Information
 - Advanced Control Foundation: Tools, Techniques and Applications ; Terrence L. Blevins, Gregory K. McMillan, Willy K. Wojsznis, Mark Nixon.
 - Advanced Control Unleashed: Plant Performance Management for Optimum Benefit; Terrence L. Blevins, Gregory K. McMillan, Willy K. Wojsznis, Michael W. Brown
- Consulting Services
 - Emerson Process Management, Industry Solutions Group
 - James Beall, <u>James.Beall@emerson.com</u>
 - John Ward, John.W.Ward@emerson.com



Thank You for Attending!

Enjoy the rest of the conference.



